










ENERGY EFFICIENT FLUORESCENT TUBE SERIES

High lumen output.
 High lumen efficiency, long life.
 Excellent color rendering.
 Energy saving, more compact and easy installation.
Application: office, restaurant, Hospital, house, shops and etc.



Type	Voltage (V)	Watts (W)	Lumens (lm)	Life (Hrs)	Temperature color (K)	CRI (Ra)	Tube Voltage (V)	Tube current (mA)	Base	Size (mm)				Primary (mm)			Master carton (mm)		
										Dia.	L	LI	D	L	W	H	L	W	H
AYDW11-U	220	11	820/880	6000	2700-6400	80/76	90	155	G27	12	220	214	27	38	21	228	405	235	253
AYDW9-U	220	9	540/580	6000	2700-6400	80/76	60	170	G27	12	150	144	27	38	21	158	500	235	183
AYDW7-U	220	7	350/380	6000	2700-6400	80/76	47	175	G27	12	120	114	27	38	21	128	500	235	153
AYDW5-U	220	5	230/240	6000	2700-6400	80/76	35	180	G27	12	90	84	27	38	21	98	500	235	126



Type	Voltage (V)	Watts (W)	Lumens (lm)	Life (Hrs)	Temperature color (K)	CRI (Ra)	Tube Voltage (V)	Tube current (mA)	Base	Size (mm)				Primary (mm)			Master carton (mm)		
										Dia.	L	LI	D	L	W	H	L	W	H
AYDN11-U	220	11	820/880	6000	2700-6400	80/76	90	155	G23	12	235	214	27	32	20	240	345	225	265
AYDN9-U	220	9	540/580	6000	2700-6400	80/76	60	170	G23	12	165	144	27	32	20	170	345	225	195
AYDN7-U	220	7	350/380	6000	2700-6400	80/76	47	175	G23	12	135	114	27	32	20	140	345	225	165
AYDN5-U	220	5	230/240	6000	2700-6400	80/76	35	180	G23	12	105	84	27	32	20	110	345	225	135