

Water proof twice 4 feet LED lights



Technical data

| Model | Light W | Length mm | Wide mm | High mm | Weight kg |
|-----------------|----------|-----------|---------|---------|-----------|
| ACWP118L | 1 x 9 w | 664 | 90 | 90 | 1.35 |
| ACWP218L | 2 x 9 w | 664 | 140 | 90 | 1.65 |
| ACWP136L | 1 x 18 w | 1274 | 90 | 90 | 1.75 |
| ACWP236L | 2 x 18 w | 1274 | 140 | 90 | 2.05 |

Performance:

- Diffuser made of transparent PS or PMMA or PC, with higher light transmittance.
- Housing made of opaque ABS or PC with good mechanical performance.
- Reflector made of painted iron plate or stainless steel plate, easy installation and maintenance.
- PG13.5 waterproof cable gland available for wiring input on one side of the housing.
- Use rubber cable 3x1 mm 2or 3x1.5mm 2 for outdoor mounting.
- Silicon gel gasket and PC clips of good mechanical performance or stainless steel clips ensuring IP65 of the lighting fixture.

Location: IP65 rated waterproof luminaire for fixed installation series, function well in waterproof and dustproof, suitable for outdoor and wet locations lighting application.

CTA International Group Pty Ltd.

Address: 67 Korong Road West Heidelberg Victoria Australia 3081

Web site: www.atd.net.au Email: info@atd.net.au

Tel: +61-03-94553991 Fax: +61-03-94553992